



Mobil Super 3000 Formula R 5W-30

Description

Mobil Super 3000 Formula R 5W-30 is high-performance very low ash engine oil designed to help prolong the life and maintain the efficiency of the Exhaust Car Emission Reduction Systems in both diesel and gasoline powered automobiles.

Features and Benefits

- Helps to maintain the efficiency of the Exhaust Emission Reduction systems in both diesel and gasoline vehicles.
- Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown.
- Provides excellent fluidity at low temperatures allowing easy winter starting and rapid oil circulation around the engine.
- Suitable for use in both gasoline and diesel engine passenger car and light commercial vehicles.

Specifications

Mobil Super 3000 Formula R 5W-30 meets or exceeds the requirements of:

ACEA	C4
------	----

Mobil Super 3000 Formula R 5W-30 has the following builder approvals:

Renault	RN0720
---------	--------

Typical Properties

Mobil Super 3000 Formula R 5W-30

Viscosity, ASTM D 445

cSt @ 40° C	68
-------------	----

cSt @ 100° C	11.7
--------------	------

Sulfated Ash, wt%, ASTM D 874	0.5
-------------------------------	-----

Phosphorous	0.05
-------------	------

Flash Point, °C, ASTM D 93	200
----------------------------	-----

Density @15° C kg/l, ASTM D 4052	0.85
----------------------------------	------

Pour Point, °C, ASTM D 97	-39
---------------------------	-----

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobil Super Motor Oil are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

9-2010

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BVBA.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA
(EMPC)
POLDERDIJKWEG
B-2030 Antwerpen
Belgium

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com. ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

© 2001-2010 Exxon Mobil Corporation. All rights reserved.