

# OFFICIALTECH

## 5W30 C4

29/05/2015  
65608

This is a full synthetic lubricant based on carefully selected very high quality base oils, specifically formulated to provide superior protection of the after-treatment systems of Renault engines.

### APPLICATIONS

Gasoline and diesel engines of passenger cars with or without turbo which are equipped with a DPF and a TWC (Three-Way Catalyst).

### FEATURES

Aftertreatment protection : full aftertreatment system protection.  
Total engine protection : outstanding engine cleanliness and durability.  
Fuel economy : lower fuel consumption and CO2 emissions.

### SPECIFICATION LEVEL

ACEA	C4-12	MB	226.51
MB	229.51	RENAULT	Approval RN 0720

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average result
Density at 15°C	ASTM D4052	g/ml	0.854
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	68
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	11,7
Viscosity index	ASTM D2270		169
B.N. (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	7.2
Pour point	ASTM D6892	°C	-39
CCS viscosity at -30°C	ASTM D5293	mPa.s	6300
Sulfated Ash	ASTM D874	Mass %	0.5
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolflubes.com](http://www.wolflubes.com)

